



# Kiosksystem T12

## DESCRIPTION:

The outdoor kiosk T12 is a robust kiosk designed for external exposure. The outdoor's rugged construction uses high quality materials and it can be used in entranceways, malls and street frontages. The sleek design can be color-customized to suit any architecture or signage, and combined with the onscreen display, can be a perfect welcome point for customers. The outdoor kiosk is ideal for transactions and can be used for hotel check in and check out, for way-finding in commercial buildings, and for any other kiosk purpose where an external presence is needed.

## CONFIGURATIONS:

- 17"/19" TFT LCD monitor
- 6mm vandal-proof, water-proof and dust-proof SAW touch screen
- Water resistant powder coat finish 16 gauge steel enclosure
- Internal heating and ventilation system
- Industrial performance embedded computer
- Cooling fans system
- 2 x 5W stereo speakers
- 90V-264V AC Industrial power supply
- Security locks/keys

## OPTIONS:

- IP65 industrial stainless steel metal keyboard with trackball
- Magnetic/smart card reader
- Omnidirectional barcode scanner
- Wireless kits
- 2 x USB ports on front
- OEM Windows XP Pro.
- SiteKiosk software
- Logo & branding graphics



## SPECIFICATIONS:

Description	Model	Kiosksystem T12	
	Definition	Floor-standing Outdoor LCD Touch Kiosk	
LCD Monitor	Screen Size	17"	19"
	Valid Area	337.920(H) x 270.336(V)mm	376.3(H) x 301.3(V) mm
	Monitor Type	TFT LCD	
	Resolution	1280×1024@75Hz	1280×1024@75Hz
	Brightness	450 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>
	Contrast Ratio	450:1	550:1
	Power Supply	12V DC/40W typical	
	Working Temp.	0°C ~ 40°C	
	Life	50000 hours	
Touch System	Technology	<input checked="" type="checkbox"/> SAW(6mm) <input type="checkbox"/> Resistive <input type="checkbox"/> IR	
	Interface	<input checked="" type="checkbox"/> Dual USB & RS232	
I/O	Audio	2 x 5W Stereo Speakers	
	I/O Ports	USB x 4, PS2 x 2, LAN port x 1, Audio in/out, VGA x 1	
Computer	Industrial Computer	Pentium M 1.8G HZ, All-in-one Mother Board, 80G HDD, 1G Memory(custom-made configuration available)	
Metal Keyboard (Optional)	Language	English or others(all country layouts available)	
	Trackball	Stainless steel or harden resin ball	
	Interface	Single USB interface for keyboard and trackball	
Magnetic/Smart Card Reader (Optional)	Card Standard	ISO 7810 and ISO 7811 and AAMVA	
	Card Speed	3 – 60 ips (7.62 – 152,4 cm/s)	
	Interface	USB, RS-232/TTL	
	Input Power	DC 5V +/- 5%	
	Head Durability	500,000 insertion cycles	
Omnidirectional Barcode Scanner (Optional)	Light Source	Visible Laser Diode(VLD)@ 650 nm	
	Depth of Field	19mm-273mm(0.75"- 10.75 ")	
	Scan Speed	1650 scan lines per second	
	No. of Scan Line	20 lines	
Overall Specification	Surface Finish	Imported Metal Paint	
	Colors	Silver grey/Black (Other colors are available)	
	Power Supply	Industrial power supply Input: 90~264V AC, 50/60 Hz	
	Power Consumption	150 Watt(typical)	
	Kiosk Dimensions(mm)	1440 x 800 x 125(H x W x D)	1620 x 800 x 125(H x W x D)
	Carton Dimension(mm)	1600 x 960 x 195(H x W x D)	1780 x 960 x 1955(H x W x D)
	Weight (N.W./G.W.)	55kgs/85kgs	65kgs/98kgs
	Operating Temp.	0°C ~ 45°C	
	Storage Temp.	-15°C ~ 60°C	
Accessories	User Guide, Power Cable, Driver CD, QC Test Report etc.		