



# Kiosksystem T22

## DESCRIPTION:

The robust floor-standing kiosk T22 represents eye-catching kiosk technology. Touch monitor options include 17" /19" LCD TFT touch screen. It is a modern-design and specially developed for check-in application in airport and metro.

## CONFIGURATIONS:

- 17"/19" TFT LCD monitor
- 6mm SAW touch screen or IR touch screen
- Vandal resistant powder coat finish 16 gauge steel enclosure
- Advertisement boarding
- Industrial performance embedded computer
- Omnidirectional barcode scanner
- Passport reader
- ID card reader
- Boarding passes printer
- Magnetic swipe card reader
- Cooling fans system
- 2 x 8W stereo speakers
- 90V-264V AC Industrial power supply
- Anti-theft locks/keys

## OPTIONS:

- Top 32"/42" TFT LCD for advertisement
- Wireless kits
- Webcam
- OEM Windows XP Pro.
- SiteKiosk software
- Logo & branding graphics



## SPECIFICATIONS:

Description	Model	Kiosksystem T22	
	Definition	Floor-standing LCD Touch Kiosk	
LCD Monitor	Screen Size	17"	19"
	Valid Area	337.920(H) x 270.336(V)mm	376.3(H) x 301.3(V) mm
	Monitor Type	TFT LCD	
	Resolution	1280×1024@75Hz	1280×1024@75Hz
	Brightness	450 cd/ m <sup>2</sup>	450 cd/ m <sup>2</sup>
	Contrast Ratio	450:1	550:1
	Power Supply	12V DC/40W typical	
	Working Temp.	0°C ~ 40°C	
	Life	50000 hours	
	Touch System	Technology	<input checked="" type="checkbox"/> SAW(6mm) <input type="checkbox"/> Resistive <input type="checkbox"/> IR
Interface		<input checked="" type="checkbox"/> Dual USB & RS232	
I/O	Audio	2 x 5W Stereo Speakers	
	I/O Ports	USB x 4, PS2 x 2, LAN port x 1, Audio in/out, VGA x 1	
Computer	Industrial Computer	Pentium M 1.8G HZ, All-in-one Mother Board, 80G HDD, 1G Memory(custom-made configuration available)	
Boarding Passes Printer	Resolution	8 dots/mm(203 dpi)	
	Print Speed	Up to 150mm/s	
	Max Print Width	ATBI size 80mm(3.15") = 640 pixels	
Magnetic Swipe Card Reader	Card Standard	ISO 7810 and ISO 7811 and AAMVA	
	Card Speed	3 – 60 ips (7.62 – 152,4 cm/s)	
	Interface	USB, RS-232/TTL	
	Input Power	DC 5V +/- 5%	
	Head Durability	500,000 insertion cycles	
Omnidirectional Barcode Scanner	Light Source	Visible Laser Diode(VLD)@ 650 nm	
	Depth of Field	19mm-273mm(0.75"- 10.75 ")	
	Scan Speed	1650 scan lines per second	
	No. of Scan Line	20 lines	
Passport Reader	MRP	2 lines of 44 characters	
	MRV	2 lines of 44 characters, 2 lines of 36 characters	
	Travel Documents	2 lines of 36 characters, 3 lines of 30 characters	
Overall Specification	Surface Finish	Imported Metal Paint	
	Colors	Silver grey/Black (Other colors are available)	
	Power Supply	Industrial power supply Input: 90~264V AC, 50/60 Hz	
	Power Consumption	150 Watt(typical)	
	Kiosk Dimensions(mm)	1460 x 497 x 505(H x W x D)	1650 x 560 x 660(H x W x D)
	Carton Dimension(mm)	1620 x 647 x 565(H x W x D)	1810 x 720 x 720(H x W x D)
	Weight (N.W./G.W.)	75kgs/105kgs	92kgs/135kgs
	Operating Temp.	0°C ~ 45°C	
	Storage Temp.	-15°C ~ 60°C	
	Accessories	User Guide, Power Cable, Driver CD, QC Test Report etc.	